Product information
Automatikgetriebereiniger

PI 40/09/30/2026



Properties
- highly economical
- gentle cleaning
- does not attack common sealing materials
- simple to use
- rapid cleaning
- assures optimum shifting performance

Technical data

Base	additive, naphtha-base special oil
Viscosity index	204
Viscosity at 40 °C	58 mm²/s
Viscosity at 100 °C	11,8 mm²/s
Form	flüssig, liquid
Odor	characteristic
Density at 15 °C	0,885 g/ml

Areas of application
For CVT, DSG and torque converter automatic transmissions.

Comment
For CVT, DSG and torque converter automatic transmissions. Follow manufacturer's instructions.

Available pack sizes

300 ml Can sheet metal	2512 DE-EN-ES-IT-PT
300 ml Can sheet metal	21515 DE-FR
300 ml Can sheet metal	21689 HU-PL-RO-TR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com