# **Product information**

PI 40/06/06/2024

# High Performance Gear Oil (GL4+) SAE 75W-90



### **Description**

High-performance, fully synthetic high-pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL-4+ is required. High-quality synthetic base oils and modern additive technology guarantee a wide application range as well as optimum transmission lubrication under extreme conditions. The low-viscosity characteristics of this gear oil make it also suitable where shifting difficulties exist (e.g. stiffness or noise generation).

# **Properties**

- excellent viscosity/temperature properties
- outstanding seal compatibility
- excellent resistance to aging
- excellent wear resistance
- high pressure-absorption capability
- wide viscosity range
- reduces gearshift resistance
- excellent corrosion protection
- reduces transmission noise

# **Specifications / Approvals**

API GL4+

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Ford ESD-M2C 175-A • VW 501 50 (G50) • ZF TE-ML 08

#### Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm³ DIN 51757
Viscosity at 40 °C	81,5 mm²/s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm²/s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	183 DIN ISO 2909
Pour point	-60 °C

**DIN ISO 3016** 

**DIN ISO 2592** 

**DIN ISO 2049** 

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

200 °C

I 1.5

Our information is based on thorough research and may be considered reliable, although not legally binding.



## Areas of application

For extreme high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL 4+ is required.

#### **Application**

The requirements of the vehicle and transmission manufacturers must be adhered to. Can be mixed with mineral oil residue, which remains in transmission/final drive when changing oil.

#### Available pack sizes

500 ml Can plastic	4433 D-GB-I-E-P
1 l Can plastic	1125 D-NL-F-GR-ARAB
1 l Can plastic	4434 D-GB-I-E-P
1 l Can plastic	20012 USA-AND-CANADA-EN-F
1 l Can plastic	20462 PL-H-RO-TR-CZ-SK
1 l Can plastic	21258 ALGERIEN-GB-ARAB-F
20 l Canister plastic	4435 D-GB-I-E-P
20 l Canister plastic	20014 USA-AND-CANADA-EN-F
60 l Black plate barrel	4436 D-GB

Flash point

Color number (ASTM)