

## Top Tec ATF 1900

### Description

Top Tec ATF 1900 is one of the new generation of high-performance oil for automatic transmissions. It is based on selected basic oils and modern, high-performance additives. The low viscosity helps to reduce the fuel consumption and increases the efficiency. The excellent stability of the friction coefficient enables extended oil change intervals.



### Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

MB 236.15

### Technical data

Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	19 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	4,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 10000 mPas ASTM D 2983-09
Viscosity index	148 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color / appearance	blue to green

### Areas of application

Developed for Mercedes-Benz 7-speed automatic transmissions of type 722.9 and 724.2 (hybrid).

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Do not mix with oils which have other specifications!

### Available pack sizes

### Available pack sizes

1 l Can plastic	3648 D-GB-I-E-P
1 l Can plastic	21267 ALGERIEN-GB-ARAB-F
1 l Can plastic	21683 GB-DK-FIN-N-S
20 l Canister plastic	3649 D-GB-I-E-P
60 l Black plate barrel	20615 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**