

Garden Winter Equipment Oil 5W-30

Description

Multigrade motor oil with high-quality base oils based on synthetic technology and a high additive content. Ensures optimum lubrication and outstanding engine cleanliness year-round, even under the most demanding conditions. Exceeds the requirements of well-known engine manufacturers such as Briggs & Stratton, Honda, Tecumseh, etc.

Properties

- no harmful effects on catalytic converters
- high resistance to aging
- low evaporation loss
- miscible with all commercially available motor oils
- very good dispersion properties
- universal application
- high wear resistance

Approvals

ACEA C3 • API SN

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	68,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≥ 6600 mPas ASTM D5293
Viscosity index	172 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,4 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049



Areas of application

For 4-stroke gasoline and diesel engines in snow blowers, lawnmowers, emergency power units, riding mowers, chippers, rotary tillers, scarifiers, string trimmers, high-pressure cleaners, etc.

Application

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Available pack sizes

1 l Can plastic 1279
D-BOOKLET

Our information is based on thorough research and may be considered reliable, although not legally binding.