

Diesel Flow Fit



Description

Combination of different high-molecular, ash-free additives. Controls the cold-dependent growth of paraffin crystals. Significantly improves the filtration properties and pour point of diesel fuel in cold weather. The effectiveness of the flow improver is dependent on the type of paraffin and the paraffin content of the medium distillates. Improves the cold filter plugging point (CFPP) by up to $-10\text{ }^{\circ}\text{C}$, depending on diesel fuel quality.

Properties

- improves filter properties
- good response behavior
- simple to use
- self mixing
- suitable for all diesel fuels (summer and winter diesel grades according to DIN EN 590) and fuel oil
- secures winter operation which would otherwise be affected by the cold

Technical data

| | |
|---|---|
| Color / appearance | cloudy |
| Density at $20\text{ }^{\circ}\text{C}$ | $0,808\text{ g/cm}^3$ |
| Flash point | $63\text{ }^{\circ}\text{C}$ |
| Improvement in filterability | up to 10, depending on diesel quality $^{\circ}\text{C}$ |
| Dosage | 150 ml portion pack sufficient for 50 - 75 litres of diesel fuel. |
| Odor | characteristic |
| Form | liquid |
| Viscosity at $40\text{ }^{\circ}\text{C}$ | $<7\text{ mm}^2/\text{s}$ |

Areas of application

For all diesel engines with and without diesel particulate filter or SCR system. Especially when treating problems. Compatible with all conventional diesel fuels and fuel oil with organic content of max. 20 %. Contents are sufficient to treat up to 75 l of fuel. Tested for compatibility with turbochargers.

Application

For optimum effect in preventing paraffin separation, it must be approx. $5\text{ }^{\circ}\text{C}$ above the cloud point (turbidity point). To improve mixing with the diesel fuel or fuel oil, add before filling up. Existing concentrations of paraffin crystals cannot be dissolved by subsequent addition.

Note: Shake can well before use. Store free of frost, where possible. Bring up to room temperature after

being affected by frost.

Available pack sizes

| | | |
|------------------------|------|----------------|
| 150 ml Can sheet metal | 1877 | D-GB-RO-RUS-UA |
| 150 ml Can sheet metal | 8344 | D-PL-BG |
| 150 ml Can sheet metal | 8929 | GB-GR-I |
| 150 ml Can sheet metal | 5130 | D-F-NL |

Our information is based on thorough research and may be considered reliable, although not legally binding.