# **Product information**

# Oil Additive

## PI 43/06/19/2023

1800 GB-GR-I



#### **Description**

Colloidal solid lubricant suspension based on molybdenum disulfide (MoS2) in mineral oil. Forms a high-load lubricating film on all rubbing and sliding surfaces. Reduces friction and ensures smoother running as well as greater engine economy. Tested for use with turbochargers and catalytic converters.



#### **Properties**

#### Technical data

Base	MoS2 -Suspension
Color / appearance	black
Solids content	~ 3 %
Density at 20 °C	0,9 g/cm³ DIN 51757
Flash point	201 °C DIN ISO 2592
Pour point	-20 °C DIN ISO 3016
Odor	characteristic
Form	liquid
Viscosity at 40 °C	95 mm²/s

#### Areas of application

Added to the lubricating oil of engines, compressors and pumps. Specially for motor vehicle engines (gasoline and diesel engines). Can be mixed with all commercially available motor oils. Suitable for toothed belts running in oil.

#### Comment

The maximum dosage for motorcycles with a wet clutch is 2 %!

#### **Application**

Shake before use. Add 5 % (50 ml per 1 l of oil) to motor oil; in motorcycles with a wet clutch add 2 % (20 ml per 1 l of oil). Can be added to the motor oil at any time.

## Available pack sizes

125 ml Can sheet metal 1011 D-F-NL

## Available pack sizes 125 ml Can sheet metal

125 ml Can sheet metal	8341 D-PL-BG
125 ml Can sheet metal	8352 D-E-P
125 ml Can sheet metal	8378 D-H-R0
125 ml Can sheet metal	21500 F-D
150 ml Can sheet metal	20628 D-E-P
200 ml Can sheet metal	1012 D-F-NL
200 ml Can sheet metal	7178 GB-GR-I
200 ml Can sheet metal	20685 D-GB-CN
300 ml Can sheet metal	2182 D-H-RO
300 ml Can sheet metal	2500 D-E-P
300 ml Can sheet metal	2591 GB-GR-I
300 ml Can sheet metal	2805 DK-N-S-FIN

300 ml Can sheet metal

300 ml Can sheet metal

7149 **GB-HEB** 300 ml Can sheet metal 8342 D-PL-BG 300 ml Can sheet metal 8350 D-F-NL

300 ml Can sheet metal 8364 GB-ARAB-F

500 ml Can sheet metal 1013 D-F-NL

5 l Canister plastic 3710

D-GB

7145

ALGERIEN-GB-ARAB-F

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

# **Product information**

Oil Additive

PI 43/06/19/2023



**Available pack sizes** 60 l Black plate barrel

20606 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com