

Motorbike 4T 10W-40 Scooter

Description

High-performance motor oil based on selected mineral oils. Ensures optimum performance and protection of the engine under all operating conditions. Reliable lubrication, optimum noise damping and low wear go without saying. Tested on engines with catalytic converters.



Properties

- miscible with all commercially available motor oils
- high shear stability
- tested for the use with catalytic converters
- high wear resistance
- optimum stability to aging
- low evaporation loss
- optimum lubrication in extreme operating conditions
- guarantees low oil consumption

Specifications

API SL • JASO MA2

Technical data

| | |
|---------------------------|---|
| SAE class (engine oils) | 10W-40 SAE J300 |
| Density at 15 °C | 0,860 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 89,0 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 13,6 mm ² /s ASTM D 7042-04 |
| Viscosity at -15 °C (CCS) | <= 7000 mPas ASTM D 5293 |
| Viscosity index | 155 DIN ISO 2909 |
| Pour point | -36 °C DIN ISO 3016 |
| Evaporation loss (Noack) | 10,0 % ASTM D 5800-08 Method B |
| Flash point | 230 °C DIN ISO 2592 |
| Total base number | 6,4 mg KOH/g DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g DIN 51575 |
| Color number (ASTM) | L 2,0 DIN ISO 2049 |

Areas of application

Developed for air and water-cooled 4-stroke engines

exposed to normal to tough operating conditions.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

| | |
|----------------------|-----------------------------|
| 1 l Canister plastic | 1618 D-BOOKLET |
| 1 l Canister plastic | 21244 ALGERIEN-GB-ARAB-F |

Our information is based on thorough research and may be considered reliable, although not legally binding.