

Motorbike Gear Oil 75W-90

Description

Fully synthetic high-pressure gear oil of API GL-5 performance class based on high-quality base oils and additives. Ensures easy, precise shifting operations and offers outstanding wear protection and optimum viscosity-temperature properties, even under extreme conditions.

Properties

- high efficiency
- excellent wear protection
- wide viscosity range
- reduces transmission noise
- good corrosion protection
- guarantees smooth gearshifting
- guarantees low fuel consumption

Specifications / Approvals

API GL5 • MIL-L 2105 C • MIL-L 2105 D

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	80 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Pour point	-57 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

For transmissions and final drives operating under maximum load. Note the transmission manufacturer's instructions.

Application

Note the transmission manufacturer's instructions. Mixable with all branded gear oils. Optimum effect only when the product is used unmixed.

Available pack sizes

Available pack sizes

500 ml Can plastic	1516 D-GB-I-E-P
500 ml Can plastic	5925 D-F-I-GR
1 l Can plastic	3825 D-GB-I-E-P
20 l Canister plastic	3826 D-GB



Our information is based on thorough research and may be considered reliable, although not legally binding.