

Touring High Tech Super SHPD 15W-40



Description

Modern multigrade motor oil. Specially developed for mixed vehicle fleets. High quality base oils and the latest additive technology guarantee maximum performance reserves and outstanding wear protection over extremely long oil change intervals. Tested on engines with catalytic converters and ideal for vehicles with and without exhaust gas turbocharger.

Properties

- extremely long oil change intervals
- suitable for all diesel engines.
- outstanding detergent and dispersant properties
- stable to ageing and stable viscosity
- excellent wear resistance
- tested for the use with catalytic converters
- prevents "bore polishing"

Approvals

ACEA E7 • ACEA A3 • ACEA B4 • API CI-4 • API SL • Allison C4 • • Global DHD-1 • JASO DH-1 • Mack EO-N • MAN M 3275-1 • MB-Approval 228.3 • Renault Trucks RLD-2 • Volvo VDS-3

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Caterpillar ECF-1-a • Caterpillar ECF-2 • Cummins CES 20076 • Cummins CES 20077 • Cummins CES 20078 • Deutz DQC III-10 • John Deere JDQ 78A • Mack EO-M Plus • MB 229.1 • MTU Typ 2 • Renault Trucks RLD

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	95 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	150 DIN ISO 2909
HTHS at 150°C	>= 3,7 mPas ASTM D5481

Technical data

Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	9 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 4,5 DIN ISO 2049

Areas of application

Suitable for universal use but especially for modern diesel engines. Also suitable for mixed vehicle fleets.

Application

Note the vehicle and engine manufacturers' operating instructions. Can be mixed with all commercially-available motor oils. Full effectiveness only when used unmixed.

Available pack sizes

5 l Canister plastic	1084 D-BOOKLET
20 l Canister plastic	1121 D-GB-I-E-P
60 l Drum sheet metal	1122 D-GB
205 l Drum sheet metal	1088 D-GB
1.000 l Container	4289 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.