Product information

PI 47/11/12/2026

LM 40 Multi-Purpose Spray



Description

Combination of active agents with corrosion protection, rust removing and water displacing properties and outstanding lubricating effect. Also improves electrical conductivity at contacts and removes dirt and stubborn oil and grease residues. Keeps moving parts in all areas from seizing up. Has a pleasant coconut fragrance.

Properties

- good water resistance
- friction and wear reducing
- good corrosion protection
- universal application
- optimum penetration properties
- silicone-free
- keeps moving parts from seizing up
- does not attack plastics, paints, metals and wood
- dissolves rust
- lubricates and maintains
- improves electrical conductivity
- releases dirt
- high load capacity

Technical data

Form	liquid
Base	combination of oils, agents
Color / appearance	brown
Odor	coco
Density at 20 °C	0,8 g/cm³
Viscosity at 40 °C	< 7 mm²/s
Operating temperature range	- 40 to + 140 °C
Spreading rate (cover)	sheet steel, bright 140-180 m²/l

Areas of application

The multipurpose product for house, hobby, workshop, vehicle and industry. For hinges, rollers, locks, bolts, switches, handles, Bowden cables, vehicle antennas and much more.

Application

Spray the area to be treated and leave it to take effect. Can also be sprayed upside down.

Available pack sizes

50 ml Can aerosol	3394 DE

Available pack sizes

200 ml Can aerosol	2815 DA-FI-NO-SV
200 ml Can aerosol	3390 DE-EN-IT
200 ml Can aerosol	8946 AR-DE-EL-FR-NL
200 ml Can aerosol	21282 AUEN-EN
400 ml Can aerosol	2816 DA-EN-FI-NO-SV
400 ml Can aerosol	3391 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com