

Brake Anti-Squeal

Description

Special lubricating and separating paste made from synthetic and ceramic agents. Eliminates squealing noises that occur between brake pistons or contact surfaces and the brake lining.

Properties

- good corrosion protection
- outstandingly adherent
- easy to use
- outstanding thermal stability
- resistant to road salt and splash water
- eliminates squeaks
- extremely low friction
- ideally suited as a separating paste

Technical data

Form	pastelike,liquid
Color / appearance	blue
Base	synthetische u. keramische Wirkstoffe
Density	1,051 g/cm ³
Operating temperature range	-40 to +200 short term +250 °C as lubricating agent -1240 °C as release agent
Flash point	>210 °C
Odor	slightly

Areas of application

For fitting, repair and maintenance work on brake systems. Used for basic lubrication and as a preventive measure against brake squeals. Highly suitable as a universal paste for numerous applications apart from brake systems.

Comment

Do not apply paste to the friction surface of the lining or the brake disk!

Shelf life in original sealed container:

10 g cushion plastic: 24 months

100 g tube plastic: 36 months

1 kg can sheet metal: 60 months

Application

With floating brake calipers, first clean all sliding



surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After the solvent has evaporated, apply the paste to the cleaned parts on all sliding surfaces, channels and contact surfaces.

Available pack sizes

10 g Cushion plastic	21121
	EN
100 g Tube plastic	3077
	DE-EN-IT
1 kg Can sheet metal	3084
	DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.