Product information

PI 51/11/12/2026

Motorbike 4T 15W-50 Street



Description

High-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear are just as much par for the course as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

Properties

- outstanding engine cleanliness
- optimum stability to aging
- high wear resistance
- high shear stability
- tested for the use with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

Specifications

API SP • JASO MA2

Technical data

SAE class (engine oils)	15W-50 SAE J 300
Density at 15 °C	0,870 g/cm³ DIN 51757
Viscosity at 40 °C	140,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	18,3 mm²/s ASTM D 7042-04
Viscosity index	145 DIN ISO 2909
Viscosity at -20 °C (CCS)	<= 7000 mPas ASTM D5293
HTHS at 150°C	≥ 3,7 mPas ASTM D 5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	10,6 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.
Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	2555 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	23228 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	1689 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	23229 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	2722 DE-EN-ES-FR-IT-PT
60 l Black plate barrel	2565 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	2566 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com