# Product information

PI 52/11/12/2026

## Motorbike Speed Shooter




### Description

Modern, ash-free combination of active ingredients with acceleration-enhancing, cleaning, dispersing, and material-protecting properties. Formulated using the latest advances in additive and fuel technology to meet the requirements of today's engines, fuels, and operating conditions. Provides a more enjoyable driving experience through optimized power output. Improves starting performance and ensures smoother engine operation.

### Properties

- higher performance gain
- improves acceleration
- prevents carburetor icing
- good corrosion protection
- removes deposits from entire fuel system
- residue-free combustion

### Technical data

| | |
|---|---|
| Base | Additive mixture in carrier fluid |
| Color / appearance | light brown |
| Density at 15 °C | 0,825 g/cm³ |
| Flash point | >63 °C |
| Odor | characteristic |
| Form | liquid |
| Viscosity at 40 °C | <7 mm²/s |

### Areas of application

For 2-stroke and 4-stroke gasoline engines (carburetor and injection).

### Available pack sizes

| | |
|---|---|
| 80 ml Can sheet metal | 7820<br>EN |
| 80 ml Can sheet metal | 8265<br>JA |
| 80 ml Can sheet metal | 20585<br>ID |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com