Product information

PI 53/11/11/2026

Motorbike 4T 10W-30 Street

Description

High-performance motor oil. For optimum lubrication, highest performance and maximum protection of the engine under all operating conditions. Ensures outstanding engine cleanliness, excellent friction values and minimum wear. Tested on engines with catalytic converters.



Properties

- outstanding engine cleanliness
- optimum stability to aging
- high wear resistance
- tested for the use with catalytic converters
- excellent shear stability
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

Specifications

API SP • JASO MA2

Technical data

SAE class (engine oils)	10W-30 SAE J 300
Density at 15 °C	0,860 g/cm³ DIN 51757
Viscosity at 40 °C	76,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	11,5 mm²/s ASTM D 7042-04
Viscosity index	145 DIN ISO 2909
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
HTHS at 150°C	⩾ 2,9 mPas ASTM D 5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	12,9 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

For air and water-cooled 4-stroke engines with and without wet clutch. Also suitable for extreme conditions and sporty use.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed.
Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	2526 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	23226 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	1688 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	23227 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	3015 DE-EN-ES-FR-IT-PT
60 l Black plate barrel	2531 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	2544 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com