

Molygen New Generation 5W-40

Description

Low-viscosity high-tech low-friction motor oil with high shear stability. Combined with innovative additive technology and the special Molygen additive. Reliably prevents the formation of deposits, reduces frictional losses in the engine and provides optimum protection against wear. The results are savings in fuel and an extended service life for the engine.

Properties

- instant lubrication after cold start
- outstanding engine cleanliness
- optimum stability to aging
- high shear stability
- miscible with all commercially available motor oils
- excellent wear protection
- friction and wear reducing
- tested for turbochargers and catalytic converters
- outstanding lubrication reliability
- excellent high and low temperature behavior

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

ACEA A3 • ACEA B4 • API SN • BMW Longlife-01 (up to 2018) • Fiat 9.55535-H2 • Fiat 9.55535-N2 • Fiat 9.55535-Z2 • GWM • HAVAL • MB 229.5 • Opel GM-LL-B-025 • Porsche A40 • Renault RN 0700 • Renault RN 0710 • VW 502 00 • VW 505 00

Technical data

SAE class (engine oils)	5W-40 SAE J 300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	90,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D 5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 Gew.-% DIN 51581



Technical data

Flash point	220 °C DIN ISO 2592
Total base number	11,3 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color / appearance	green, fluorescent

Areas of application

Best for modern gasoline and diesel engines with and without exhaust gas turbochargers. For the protection and value retention of the engine during long intervals between oil changes and with high loads.

Application

Note the vehicle and engine manufacturers' operating instructions. Can be mixed with all commercially available motor oils. Full effectiveness only achieved when the product is not mixed.

Available pack sizes

1 l Canister plastic	8576 AR-BG-CS-DA-EL-EN-ES-FI- FR-HR-HU-ID-IT-KK-NL-NO- PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	20991 DE-EN-ZH
1 l Canister plastic	21242 AR-DZAR-EN-FR
4 l Canister plastic	8578 AR-BG-CS-DA-EL-EN-ES-FI- FR-HR-HU-ID-IT-KK-NL-NO- PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	20993 DE-EN-ZH
5 l Canister plastic	8536 AR-BG-CS-DA-EL-EN-ES-FI- FR-HR-HU-ID-IT-KK-NL-NO- PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21329 DE-EN-ES-IT-PT

Molygen New Generation 5W-40

Available pack sizes

60 l Black plate barrel	9056 DE-EN
205 l Black plate barrel	9057 DE-EN

**Our information is based on thorough research
and may be considered reliable, although not
legally binding.**