Product information

PI 67/11/11/2026

Motorbike 4T 10W-40 Street

Description

High-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimal lubrication, excellent engine cleanliness, favorable friction properties, and minimal wear are as much a given as smooth clutch engagement and disengagement, and smooth shifting. Tested on engines with catalytic converters.



Properties

- outstanding engine cleanliness
- optimum stability to aging
- high wear resistance
- high shear stability
- tested for the use with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

Specifications

API SP • JASO MA2

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,860 g/cm³ DIN 51757
Viscosity at 40 °C	96,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	14,6 mm²/s ASTM D 7042-04
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
HTHS at 150°C	⩾ 3,5 mPas ASTM D 5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	238 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049
Oil base	Advanced Full Synthetic

Areas of application

Designed for air and water-cooled 4-stroke engines operating under normal to high-load conditions. For sporting applications. Suitable for engines with or without without wet clutches.

Application

Follow the engine manufacturer's operating instructions.
Note: For optimal effectiveness, use only unmixed.

Available pack sizes

1 l Canister plastic	1521 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	1755 JA
1 l Canister plastic	21246 AR-DZAR-EN-FR
1 l Canister plastic	23224 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	1243 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	23225 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	1562 DE-EN-ES-FR-IT-PT
60 l Black plate barrel	1563 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	1568 DE-EN-ES-FR-IT-PT
1.000 l Container	21806 DE-EN

Our information is based on thorough research and may be considered reliable, although not

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Motorbike 4T 10W-40 Street

PI 67/11/11/2026

legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com