Product information
Ceramic Powder Spray

PI 8/11/12/2026



Description
Grease-free lubricant and release agent based on hexagonal boron nitride. Suitable for virtually all materials. Provides care, protection, and insulation, eliminates squeaking, and is highly versatile thanks to its long-lasting lubricating properties. Especially suitable where oil- or silicone-based products may affect subsequent processes, such as painting.

Properties
- universal application
- fast-drying
- dirt repellent
- excellent adhesion
- boron nitride is chemically resistant
- wide operating temperature range
- noise absorbing
- silicone-free

Technical data

Color / appearance	white
Base	ceramic solid lubricants
Operating temperature range	-80 to +900 °C
Propellant	propane, butane
Form	liquid
Odor	characteristic

Areas of application
Ideal for lubricating belt mechanisms and guide rails, e.g. on seat frames. Also suitable as a lubricant and release agent, in textile and wood processing for bearings, slide rails, rollers, chains and threads, universally in the household and as a release agent in plastics processing.

Application
Shake can for at least 30 seconds before use. Then spray a thin and even layer onto the previously cleaned, grease-free and dry surface. If greater layer thickness is required, the most recently applied coat must be allowed to dry completely. Note: After use, clear spray nozzle by holding can with spray head upside down and spraying until only pure propellant emerges.

Available pack sizes

400 ml Can aerosol	21919 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com