

Top Tec ATF 1800

Description

Low-viscosity high-performance oil of the new generation for automatic transmissions. It is based on synthesis technology with modern, high-performance additives. Aside from excellent ageing and oxidation stability, optimal shifting is guaranteed under all operating conditions thanks to the extremely high viscosity index. It enables long oil change intervals.

Properties

- excellent viscosity/temperature properties
- prevents foam formation
- enables a multifaceted range of applications
- outstanding friction characteristics
- high resistance to aging
- very good low-temperature properties
- excellent corrosion protection
- high wear resistance
- outstanding resistance to oxidation

Approvals

Dexron VI • Ford Mercon LV

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Aisin Warner AW-1 • BMW 83 22 0 142 516 • BMW 83 22 2 152 426 • BMW 83 22 2 289 720 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 355 599 • BMW M-1375.4 • Fiat 9.55550-AV5 • Honda ATF 3.1 • Honda DW-1 • Hyundai SP-IV • Hyundai SP-IV-RR • Isuzu ATF WSI • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Mazda ATF FZ • MB 236.12 • MB 236.14 • Mitsubishi Dia Queen ATF-PA • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 162 • VW G 055 540 • VW G 060 162

Technical data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	28,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,8 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	≤ 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592



Technical data

Color / appearance	bräunlich/brownish
Color number (ASTM)	4
	DIN ISO 2049

Areas of application

Primarily developed for automatic transmissions of various manufacturers such as Aisin Warner, ZF etc., which are installed in various vehicles of Audi, BMW, Ford, Honda, Hyundai, Jeep, Jaguar, Kia, Land Rover, Lexus, Mazda, Mercedes-Benz, Mini, Opel, Peugeot, Porsche, Toyota, VW, Volvo etc. Meets further manufacturer specifications, allowing it to cover an even wider range of vehicles.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Can plastic	3687 D-GB-I-E-P
1 l Can plastic	9704 D-GB-F-ARAB
1 l Can plastic	20461 D-PL-H-RO-TR
1 l Can plastic	21234 ALGERIEN-GB-ARAB-F
1 l Can plastic	21107 D-GB-CN
5 l Canister plastic	20662 D-GB-I-E-P
5 l Canister plastic	21256 ALGERIEN-GB-ARAB-F
20 l Canister plastic	3688 D-GB-I-E-P
60 l Drum sheet metal	3689 D-GB

Product information

PI 91/12/01/2021



Top Tec ATF 1800

Available pack sizes

205 l Drum sheet metal 20624
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.