Product information

PI 11/10/11/2024

Pro-Line Engine Protection



Description

Highly effective additive formulated with concentrated MoS_2. Ensures immediate friction and wear reduction, adds an extremely protective and pressure-resistant boundary layer with low friction and protects during cold starts as well as under extreme operation conditions to prevent damage from lack of oil. Contributes to lower fuel consumption, longer engine life and less wear. Specifically designed for engines with large oil volumes and heavy load.

Technical data

Color / appearance	black
Base	solvent raffinate
Operating temperature range	as with other mineral MoS2: above 752 °F
Solids content	5 %
Form	liquid
Odor	characteristic
Density at 68 °F	0,92 g/ml
Flash point	392 °F
Viscosity at 104 °F	290-300 mm²/s

Areas of application

Use in all 4-stroke gas and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

Comment

Not suitable for use in motorcycles with wet clutches!

Application

One full can (1 l) used with 30-50 liters (32 – 53 U.S. Qts) of motor oil. The product is self-mixing and can be added at any time. For best protection, use with every oil change.

Available pack sizes

1 l Can sheet metal	22247 USA-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com