

Pro-Line Turbocharger Additive

Description

Provides initial lubrication of new or replaced turbochargers to prevent damage due to oil starvation. Damage to turbocharger may occur within seconds of engine start if not lubricated properly. Pro-Line Turbocharger additive will provide needed protection and allow proper break-in of new units which prevents additional repairs.



and may be considered reliable, although not legally binding.

Properties

- outstanding emergency-running properties
- protects against damage caused by lack of oil in the running-in phase
- miscible with all commercially available motor oils
- increases operational reliability

Technical data

Color / appearance	dark grey - black
Solids content	~ 10 %
Viscosity at 68 °F	304,31 mPas DIN 51398
Flash point	> 212 °F DIN ISO 2592
Pour point	5 °F DIN ISO 3016
Thermal stability	> 752 °F
Form	liquid
Odor	characteristic
Density at 68 °F	1,0013 g/cm ³

Areas of application

For all 4-stroke gasoline and diesel engines. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

Application

The oil intake passage of the turbocharger is filled to the brim with Pro-Line Turbocharger Additive before the oil supply line is connected.

Available pack sizes

20 g Tube plastic 22074
USA-EN

Our information is based on thorough research