

## Motorbike Shock Absorber Oil RACE

### Description

Fully synthetic shock absorber oil. Prevents deposit build-up while reducing friction and wear. Foaming is prevented even during extreme conditions. The unique formulation allows better handling and rider feedback which allows easier suspension tuning. Fluid color is blue.

### Properties

- increases driving safety
- high wear resistance
- outstanding viscosity stability
- prevents build-up of deposits
- very compatible with seals
- outstanding corrosion protection
- prevents foam formation

### Technical data

Density at 59 °F	0,825 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	17,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	3,95 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	124 DIN ISO 2909
Demulgation characteristics at 129 °F	< 20 min DIN ISO 6614
Pour point	-81 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Color / appearance	blue

### Areas of application

Designed for racing or extreme motorbike and powersports use and when a fluid according to current product specifications is required or recommended.

### Comment

**⚠ WARNING: Cancer-** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted. Professional use only.

### Available pack sizes

1 l Can plastic	20290 USA-AND-CANADA-EN-F
-----------------	------------------------------

### Available pack sizes

20 l Canister plastic 20292  
USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

