

Description

For the lubrication of pneumatic equipment via compressed air service units or oil-fog lubricators.

Properties

- lasting corrosion protection
- excellent wear resistance
- excellent low temperature behavior
- excellent resistance to aging

Technical data

SAE class (engine oils)	10W SAE J300
Density at 59 °F	0,86 g/cm ³ DIN 51757
Viscosity at 104 °F	38 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,6 mm ² /s ASTM D 7042-04
Viscosity at -22 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -13 °F (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	130 DIN ISO 2909
Pour point	-38 °F DIN ISO 3016
Evaporation loss (Noack)	10 % CEC-L-40-A-93
Flash point	428 °F DIN ISO 2592
Total base number	10,3 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

For lubrication and extension of the service life of the respective pneumatic tools used in compressed air service units or oil-fog lubricators.

Application

Fill oil for pneumatic equipment in the compressed air service unit or in the oil-fog lubricator up to the max. marking on the inspection glass. The manufacturer's filling instructions must be observed!

Available pack sizes



Available pack sizes

50 ml Can plastic 7841
D

Our information is based on thorough research and may be considered reliable, although not legally binding.