

## Multi-disc Clutch Oil

### Description

High performance gear oil specially developed for Haldex all-wheel drive, Quattro and 4motion drives. Provides excellent viscosity and shear stability as well as outstanding friction coefficient under all operating conditions. Protects reliably against wear, foaming and corrosion. Ensures optimum power transmission on all-wheel drive vehicles.



### Properties

- excellent wear resistance
- excellent shear stability
- optimum friction coefficient under all operating conditions
- reliable protection against foaming
- extremely high viscosity index
- outstanding corrosion protection

### Available pack sizes

1 l Can plastic 22194  
USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

GM • Opel • Volvo • VW G 052 175 (TL 52175) • VW G 055 175 (TL 52175-X) • VW G 060 175 (TL 52175-Y)

### Technical data

|                     |                                           |
|---------------------|-------------------------------------------|
| Density at 59 °F    | 0,85 g/cm <sup>3</sup><br>DIN 51757       |
| Viscosity at 104 °F | 27,5 mm <sup>2</sup> /s<br>ASTM D 7042-04 |
| Viscosity at 212°F  | 5,7 mm <sup>2</sup> /s<br>ASTM D 7042-04  |
| Viscosity index     | 155<br>DIN ISO 2909                       |
| Pour point          | -76 °F<br>DIN ISO 3016                    |
| Flash point         | 446 °F<br>DIN ISO 2592                    |
| Color / appearance  | gelblich                                  |

### Areas of application

For all-wheel drive systems with Haldex coupling where a fluid according to current specifications is required or recommended to use.

### Comment

**⚠ WARNING: Reproductive Harm -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Application

Observe the manufacturers instructions!

### Available pack sizes