Product information

Top Tec 6610 SAE 0W-20

PI 18/03/14/2022 LIQU

Description

Fully synthetic superior low friction motor oil. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high shear stability
- saves fuel and reduces pollutant emissions
- high lubrication reliability
- optimum stability to aging
- excellent high and low temperature behavior
- long engine service life
- optimum oil pressure under all operating conditions
- ideal with turbochargers and catalytic converters

Approvals

ACEA C5 • API SP • Ford WSS-M2C 952-A1 • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel 0V0401547

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

GM dexos D

Technical data

SAE class (engine oils) 0W-20

SAE J300

Density at 59 °F 0,845 g/cm³

DIN 51757

Viscosity at 104 °F 39 mm²/s

ASTM D 7042-04

Viscosity at 212°F 8 mm²/s

ASTM D 7042-04

Viscosity at -40 °F (MRV) < 60000 mPas

ASTM D 4684

Viscosity at -31 °F (CCS) ≤ 6200 mPas

ASTM D 5293

Viscosity index 185

DIN ISO 2909

HTHS at 302 °F ≥ 2.6 mPas

ASTM D 5481

Pour point -43 °F

DIN ISO 3016



Technical data

Evaporation loss (Noack) 11 %

CEC-L-10-A-93

Flash point 428 °F

DIN ISO 2592

Total base number 9,5 mg KOH/g

DIN ISO 3771

Sulfate ash ≤ 0,8 %

DIN 51575

Color number (ASTM) L 3,0

DIN ISO 2049

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

5 l Canister plastic 22190

USA-AND-CANADA-EN-F

20 l Canister plastic 22192

USA-AND-CANADA-EN-F

205 l Black plate barrel 22193

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com