

## Top Tec 6610 SAE 0W-20

### Description

Fully synthetic superior low friction motor oil. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanliness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

### Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear protection
- high shear stability
- saves fuel and reduces pollutant emissions
- high lubrication reliability
- optimum stability to aging
- excellent high and low temperature behavior
- long engine service life
- optimum oil pressure under all operating conditions
- ideal with turbochargers and catalytic converters

### Specifications / Approvals

ACEA C5 • API SP • Ford WSS-M2C 952-A1 • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel OV 040 1547 - A20

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

GM dexos D

### Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 59 °F	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	39 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 302 °F	≥ 2,6 mPas ASTM D 5481
Pour point	-43 °F DIN ISO 3016



### Technical data

Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	428 °F DIN ISO 2592
Total base number	9,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

### Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

### Application

Observe the manufacturers instructions!

### Available pack sizes

5 l Canister plastic	22190 USA-AND-CANADA-EN-F
20 l Canister plastic	22192 USA-AND-CANADA-EN-F
205 l Black plate barrel	22193 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**