

Product information

Meguin Gleitoel CGLP 150



Specifications and approvals

Schmieröl DIN 51502 CGLP 150

Characteristic data

ISO viscosity class	VG 150 DIN 51519
Density at 59 °F	0,895 g/cm ³ DIN 51757
Viscosity at 104 °F	150 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,7 mm ² /s ASTM D 7042-04
Viscosity index	97 DIN ISO 2909
Pour point	-18 °F DIN ISO 3016
Flash point	256 °F DIN ISO 2592
Foaming behavior at 75 °F	0/0 ml ISO 6247
Foaming behavior at 200 °F	0/0 ml ISO 6247
Foaming behavior at 75 °F after 200 °F	0/0 ml ISO 6247
Corrosion effect on steel	0-A DIN ISO 7120
Corrosion effect on copper	1-100 A3 DIN EN ISO 2160
Sulfate ash	0,3 g/100g DIN 51575
FZG gear rig test, standard test A/8, 3/90	Schadenskraftstufe >12, Spez.Gew.Änderung <0,3 mg/KWh DIN 51354 Teil 2
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

20 l Canister plastic	8655 D-GB
200 l Drum sheet metal	8656 D-GB