

## Special Tec LR SAE 0W-20



### Description

Fully synthetic top-of-the-line, low friction motor oil. Developed specifically for use in numerous Jaguar and Land Rover vehicles. Low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

### Properties

- smooth engine running
- outstanding engine cleanliness
- excellent wear resistance
- high lubrication reliability
- long engine service life
- high shear stability
- saves fuel and reduces pollutant emissions
- optimum stability to aging
- excellent high and low temperature behavior
- optimum oil pressure under all operating conditions
- tested for turbochargers and catalytic converters
- miscible with all commercially available motor oils

### Specifications and approvals

ACEA C5 • API SN • Jaguar / Land Rover  
STJLR.51.5122

### Technical data

SAE Viscosity	0W-20 SAE J300
Density at 59 °F	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	39,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	8,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	< 6200 mPas ASTM D 5293
Viscosity index	193 DIN ISO 2909
HTHS at 302 °F	≥ 2,6 mPas ASTM D 5481
Pour point	-48 °F DIN ISO 3016
Flash point	226 °F DIN ISO 2592
Evaporation loss (Noack)	11,9 % ASTM 5800B
Total base number	7,9 mg KOH/g DIN ISO 3771

### Technical data

Color / appearance	bräunlich
Sulfate ash	0,8 % DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

### Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

### Application

Observe the manufacturers instructions!

### Available pack sizes

1 l Canister plastic	20408 USA-AND-CANADA-EN-F
5 l Canister plastic	20410 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**