

Oil Binder

Description

Powerful 100 % polyurethane hard foam-based oil absorbent. Absorbs all oil-based fluids but will not retain water which makes it more efficient when cleaning oil spills, especially in a wet environment. Use to clean oil, fuel and water repellent fluids. May be used indoors or outdoors. Safe for use in almost any industry including fire dept. and tow services.



Technical data

Form	granular
Color / appearance	light brown, light yellow
Base	polyurethane
Grain size	0,5 – 4 mm
Odor	odourless
Oil absorbency, per liter oil and chemical binder	1 litre binds ca. 0.6 litres of oil
Apparent density	~296 g/l
Storage stability	>5 years
Flash point	~300 °F

Areas of application

Suitable for small to large spillage, indoor or outdoor. Equally effective on wet or dry surface.

Application

Always check compatibility with spilled liquid before using LIQUI MOLY Oil Binder. Apply a 5mm (3/16") thick layers of Oil Binder onto the spilled liquid and allow sufficient time to absorb. For faster absorption use a firm bristle broom to sweep material back and forth across the spilled liquid. Be advised that dust may be created when applying to spill area. For complete spill removal more than one application may be required. Always dispose of properly, check local regulations regarding waste disposal.

Available pack sizes

25 l Carton 7250
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.