

## Marine High Performance Gear Oil SAE 85W-90

### Description

Special high-performance gear lube specifically for marine use. Formulated with a unique additive package that guarantees outstanding wear protection even if contaminated with water. Stable under extreme pressure, high stress and at high speeds. Offers outstanding corrosion protection and very good oxidation resistance. Fluid color is blue.



### Properties

- outstanding corrosion protection
- high pressure-absorption capability
- excellent viscosity/temperature properties
- stable to aging and stable viscosity
- excellent high-pressure and wear protection properties

### Technical data

SAE class (gear oils)	85W-90 SAE J 306
Density at 59 °F	0,88 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	163,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	15,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 10 °F (Brookfield)	<= 150000 mPas ASTM D 2983-05
Viscosity index	96 DIN ISO 2909
Pour point	-16 °F DIN ISO 3016
Flash point	435 °F DIN ISO 2592
Color / appearance	blue

### Areas of application

For transmissions where a high-performance gear lube with current product specifications is required or recommended. Specifically suited for Mercury outboard motors as of 75 hp output as well as MerCruiser Z-drives. Can be used as a replacement for a high-performance gear lube with viscosity SAE 90.

### Comment

**⚠ WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Application

Observe the manufacturers instructions!

### Available pack sizes

1 l Can plastic	20536 USA-AND-CANADA-EN-F
20 l Canister plastic	20492 USA-AND-CANADA-EN-F
60 l Black plate barrel	20493 USA-AND-CANADA-EN-F
205 l Black plate barrel	22524 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**