Product information

PI 21/03/25/2025

DPF Pressurized Tank Spray Gun



Description

The Spray-Gun is powder coated for protection and equipped with a non-return pressure valve. It comes supplied with a European style hose coupling. Reservoir size is 1 liter (34 FL OZ). The built-in manual flow valve allows precise control of spray volume. The Liqui Moly spray gun design provides a finely atomized spray pattern for a more efficient DPF cleaning.

Technical data

Operating pressure	2-8 bar
Maximum pressure	8 bar
required air quality	filtered, free of condensate

Areas of application

Designed for use together with Liqui Moly DPF-Probe (LM7945) and when applying Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge. Operating air pressure is 6-8 bar (90 - 120 psi).

Comment

CAUTION: Always depressurize and drain after each use and before storing.

Application

Designed for use together with Liqui Moly DPF-Probe (LM7945) and when applying Pro-Line Diesel Particulate Filter Cleaner and Pro-Line Diesel Particulate Filter Purge.

Available pack sizes

1 pcs Carton	7946 D

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com