

**Motorbike Fork Oil SAE 7,5W medium/light****Description**

Full synthetic, medium/light viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

**Properties**

- good corrosion protection
- prevents seals from swelling
- prevents foam formation
- high wear resistance
- increases driving safety

**legally binding.****Technical data**

Density at 59 °F	0,825 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	22,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	4,75 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	139 DIN ISO 2909
Pour point	-65 °F DIN ISO 3016
Flash point	453 °F DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

**Areas of application**

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

**Application**

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

**Available pack sizes**

1 l Can plastic	20098 USA-AND-CANADA-EN-F
20 l Canister plastic	20403 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not**