

Motorbike Fork Oil SAE 10W medium

Description

Full synthetic, medium-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.



Properties

- prevents seals from swelling
- prevents foam formation
- good corrosion protection
- high wear resistance
- better drivability

legally binding.

Technical data

| | |
|---------------------|--|
| Density at 59 °F | 0,83 g/cm ³ ASTM D 7042-04 |
| Viscosity at 104 °F | 28,5 mm ² /s DIN 51757 |
| Viscosity at 212°F | 5,7 mm ² /s ASTM D 7042-04 |
| Viscosity index | 146 DIN ISO 2909 |
| Pour point | -43 °F DIN ISO 3016 |
| Flash point | 471 °F DIN ISO 2592 |
| Color number (ASTM) | L 0,5 DIN ISO 2049 |

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

| | |
|-----------------------|------------------------------|
| 1 l Can plastic | 20092 USA-AND-CANADA-EN-F |
| 20 l Canister plastic | 20404 USA-AND-CANADA-EN-F |

Our information is based on thorough research and may be considered reliable, although not