

Top Tec MTF 5100 SAE 75W

Description

Low-viscosity high-performance transmission fluid. High shear stability provides low fuel consumption and excellent wear protection. Outstanding resistance to viscosity breakdown provides superior shift performance in all operating conditions. Suitable for a variety of transmissions.



Properties

- outstanding shifting comfort under all operating conditions
- guarantees low fuel consumption
- excellent shear stability
- excellent wear resistance
- outstanding corrosion protection
- excellent viscosity/temperature properties
- excellent synchronous behavior
- outstanding resistance to oxidation

Specifications and approvals

API GL4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW 83 22 7 533 818 • BMW MTF LT-3 • Fiat 9.55550-MZ6 • Ford WSS-M2C 200-D2 • Toyota • VW G 052 178 • VW G 052 512 • VW G 052 726 • VW G 055 512 • VW G 060 726 • VW G 070 726

Technical data

SAE class (gear oils)	75W SAE J 306
Density at 59 °F	0,86 g/cm ³ DIN 51757
Viscosity at 104 °F	33,1 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	< 150000 mPas ASTM D 2983-09
Viscosity index	130 DIN ISO 2909
Pour point	-42 °F DIN ISO 3016
Flash point	224 °F DIN ISO 2592
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

Universal use in modern gearboxes and specific dual-clutch transmissions (DCT). Suitable for numerous BMW and Volkswagen / Audi vehicles as well as for transmissions from other manufacturers where a gear oil meeting current product specification is required or recommended.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Can plastic	20352 USA-AND-CANADA-EN-F
20 l Canister plastic	20354 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.