

Description

An effective mixture of additives for rapid removal of performance dimishing deposits from the fuel system in all kinds of diesel engines. Cleans injectors, the combustion chamber and restores proper fuel atomization for improved engine efficiency.

Properties

- removes deposits from entire fuel system
- eliminates diesel knocking
- suitable for all diesel engines, including common rail
- increases cetane number
- reduces pollutant emissions
- for problem-specific use

Technical data

Base	additive, carrier fluid
Color / appearance	light brown, clear
Density at 59 °F	0,869 g/cm³
Flash point	63 °F
Viscosity at 104 °F	< 7,0 mm²/s
Odor	characteristic
Form	liquid

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

Comment #P65 **WARNING:** Cancer and Reproductive Harmwww.P65Warnings.ca.gov

Application

To be added directly into the fuel tank. Use as preventive or to cure acute engine problems. The product mixes with the fuel automatically. Contents (500 mL) is sufficient for 25–115 Liters (7 gal. to 30 gal.) fuel.

Available pack sizes

500 ml Can sheet metal 20252 USA-EN

Our information is based on thorough research



and may be considered reliable, although not legally binding.