

Motorbike Gear Oil SAE 10W-30

Description

Synthetic, high-performance API GL4 gear oil. Facilitates smooth and precise shifting under all operating conditions, provides reliable wear protection properties and ideal viscosity-temperature behavior.

Properties

- excellent viscosity/temperature properties
- very compatible with seals
- high pressure-absorption capability
- excellent resistance to aging
- minimizes wear
- reduces running noise

Specifications and approvals

API GL4

Technical data

SAE class (engine oils)	10W-30 SAE J 300
Density at 59 °F	0,86 g/cm ³ DIN 51757
Viscosity at 104 °F	76 mm ² /s ASTM D 7042-04
Viscosity at 212°F	11,5 mm ² /s ASTM D 7042-04
Viscosity at -22 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -13 °F (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	145 DIN ISO 2909
HTHS at 302 °F	>= 2,9 mPas ASTM D5481
Pour point	-39 °F DIN ISO 3016
Evaporation loss (Noack)	12,9 % CEC-L-40-A-93
Flash point	230 °F DIN ISO 2592
Total base number	7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

Universal use in motorbike transmissions and final drives where a gear oil according to current product



specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Available pack sizes

1 l Can plastic 20090
USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.