

Product information

Battery Clamp Grease

PI 29/09/25/2021



Description

Protects battery terminals and electrical contacts from corrosion and oxidation. It is compatible with most plastics, ensures safe starting, bright light and longer battery life. Prevents acid damage, leakage current and contact resistance. Certification: acc DIN 51502 K2G-30



Technical data

| | |
|---|---|
| Saponification type | Calciumseife |
| Brief description | K2G-30 DIN 51502 |
| NLGI number | 2 DIN 51818 |
| Color / appearance | red |
| Worked penetration | 265-295 1/10 mm DIN ISO 2137 |
| Dropping point | 145 °F DIN ISO 2176 |
| Oil separation after 7 days at 104 °F | 3,6 % DIN 51817 |
| Oil separation after 18 hours at 104 °F | 1,1 % DIN 51817 |
| Flow pressure at -22 °F | <1400 mbar DIN 51805 |
| Emcor corrosion class | 0/0 DIN 51802 |
| Copper corrosion after 24 hours at 212 °F | 1:00 AM DIN 51811 |
| Behavior in the presence of water | 0-40 DIN 51807 Teil 1 |
| Base oil | |
| Viscosity at 104 °F | 32 mm ² /s ASTM D 7042-04 |
| Flash point | 200 °F DIN ISO 2592 |
| Pour point | -21 °F DIN ISO 3016 |
| Density | 0,894 g/cm ³ |

Available pack sizes

50 pdf.measure.g Tube Kunststoff 20244
USA-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Use on battery terminals and connectors along with terminal connectors in vehicle electronics.

Application

Clean contaminated components and treat with Battery Clamp Grease.

Available pack sizes