

## Motorbike HD-Classic SAE 50 Street

### Description

Single-grade motor oil. For use in classic motorcycles. Specifically recommended for Harley Davidson when a single grade oil is needed. High wear resistance and outstanding corrosion protection. Absolute shear stability. Provides quiet engine running and long engine life. Low volatile loss and oil consumption.



### Properties

- very good dispersion properties
- high wear resistance
- excellent cleaning effect
- high shear stability
- optimum stability to aging
- guarantees low oil consumption
- low evaporation loss
- outstanding oil film strength
- miscible with all commercially available motor oils

### Approvals

API SG

### Technical data

|                          |   |
|--------------------------|---|
| SAE class (engine oils)  | 50<br>SAE J300                            |
| Density at 59 °F         | 0,9 g/cm <sup>3</sup><br>DIN 51757        |
| Viscosity at 104 °F      | 225 mm <sup>2</sup> /s<br>ASTM D 7042-04  |
| Viscosity at 212°F       | 20,5 mm <sup>2</sup> /s<br>ASTM D 7042-04 |
| Viscosity index          | 105<br>DIN ISO 2909                       |
| Pour point               | 0 °F<br>DIN ISO 3016                      |
| Evaporation loss (Noack) | 4 %<br>CEC-L-40-A-93                      |
| Flash point              | 482 °F<br>DIN ISO 2592                    |
| Total base number        | 11 mg KOH/g<br>DIN ISO 3771               |
| Sulfate ash              | 1,2 g/100g<br>DIN 51575                   |
| Color number (ASTM)      | L 4,5<br>DIN ISO 2049                     |

### Areas of application

Harley Davidson specific oil usable in all 4-stroke engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or

recommended. Safe with catalytic converters.

### Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

**Our information is based on thorough research and may be considered reliable, although not legally binding.**