

Marine Super Diesel Additive

Description

A combination of additives that clean and maintain diesel fuel systems. Prevents corrosion and increases lubrication thus reducing fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order. Protects against the negative effects of too high proportion of water in fuel systems.

Properties

- increases cetane number
- keeps the fuel system clean
- optimizes engine performance
- keeps injection nozzles clean
- guarantees low fuel consumption
- high wear resistance
- prevents build-up of deposits
- increases lubricating
- prevents seizing and injector gumming

Technical data

Base	additive mixture in carrier fluid
Color / appearance	yellowish brown
Density at 59 °F	0,87 g/cm ³
Hazard class as per German VbF	A III
Flash point	145 °F
Pour point	-32 °F

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

Comment

⚠ WARNING: Cancer - www.P65Warnings.ca.gov.

Application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF). To be added directly into the fuel tank, ideal for long-term use with every refueling. 500 ml is sufficient for up to 250 Liters (66 gal.) / 1 Liter is sufficient for up to 500 Liters (132 gal.) diesel fuel (mixing ratio up to 1: 500).

Available pack sizes

500 ml Can sheet metal	20526 CANADA-EN-F
------------------------	----------------------

Available pack sizes

500 ml Can sheet metal	20550 USA-EN
1 l Can sheet metal	20552 USA-EN



Our information is based on thorough research and may be considered reliable, although not legally binding.