

## Top Tec ATF 1600

### Description

Fully synthetic automatic transmission fluid, developed for exclusive use in 1st generation Mercedes-Benz 7-speed automatic transmission (up to June 2010) and also compatible with various older Mercedes-Benz 5-speed automatic transmission requirements. Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a red color.

### Properties

- excellent corrosion protection
- excellent wear resistance
- prevents foam formation
- excellent viscosity/temperature properties
- very good low-temperature properties
- outstanding resistance to oxidation
- for eliminating shifting problems
- outstanding friction characteristics
- excellent resistance to aging

### Approvals

MB-Approval 236.14

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

MB 236.12

### Technical data

Density at 59 °F	0,85 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	28,7 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	6,45 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	188 DIN ISO 2909
Flash point	402 °F DIN ISO 2592
Pour point	-49 °F DIN ISO 3016
Color / appearance	rot

### Areas of application

For Mercedes-Benz automatic transmissions where a ATF fluid meeting current product specifications is required or recommended.



### Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

### Available pack sizes

1 l Can plastic	20024 USA-AND-CANADA-EN-F
20 l Canister plastic	20026 USA-AND-CANADA-EN-F
205 l Drum sheet metal	22163 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**