

Special Tec V SAE 0W-30

Description

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

Properties

- high shear stability
- saves fuel and reduces pollutant emissions
- ideal with turbochargers and catalytic converters
- optimum stability to aging
- outstanding engine cleanliness
- high lubrication reliability
- instant lubrication after cold start

Specifications and approvals

ACEA A5 • ACEA B5 • API SL • API CF • ILSAC GF-3 • Volvo VCC 95200377

Technical data

SAE class (engine oils)	0W-30 SAE J300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	51,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,9 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	182 DIN ISO 2909
HTHS at 302 °F	2,9 - 3,5 mPas ASTM D 5481
Pour point	-48 °F DIN ISO 3016
Evaporation loss (Noack)	12,5 % CEC-L-40-A-93
Flash point	226 °F DIN ISO 2592
Total base number	11,1 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 1,6 g/100g DIN 51575



Technical data

Color number (ASTM)	3
	DIN ISO 2049

Areas of application

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic	20202 USA-AND-CANADA-EN-F
5 l Canister plastic	20204 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.