

Molygen New Generation SAE 5W-20

Description

Fully synthetic LIQUI MOLY specialty with a unique additive technology. The powerful MFC (Molecular Friction Control) technology prevents formation of deposits while simultaneously reducing frictional losses. The synergetic effect provides optimum wear protection even under tough operating conditions. Improved fuel consumption and increased engine life are some of the end results. The oils fluorescent green color is typical for the MFC formulation.

Properties

- smooth engine running
- optimum oil pressure under all operating conditions
- long engine service life
- reduces pollutant emissions
- ideal with turbochargers and catalytic converters
- excellent wear protection
- high lubrication reliability
- outstanding engine cleanliness
- instant lubrication after cold start
- optimum stability to aging
- excellent low temperature behavior
- reduces fuel consumption
- miscible with all commercially available motor oils

Specifications / Approvals

API SP • ILSAC GF-6A

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford WSS-M2C 930-A • Ford WSS-M2C 945-A • Ford WSS-M2C 945-B1 • Ford WSS-M2C 960-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Hyundai • Kia • Mazda • Mitsubishi • Mitsubishi Dia Queen • Nissan • Subaru • Toyota

Technical data

SAE class (engine oils)	5W-20 SAE J300
Density at 59 °F	0,85 g/cm ³ DIN 51757
Viscosity at 104 °F	50,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	8,8 mm ² /s ASTM D 7042-04
Viscosity at -31 °F (MRV)	< 60000 mPas ASTM D 4684



Technical data

Viscosity at -22 °F (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	154 DIN ISO 2909
HTHS at 302 °F	>= 2,6 mPas ASTM D 5481
Pour point	-54 °F DIN ISO 3016
Evaporation loss (Noack)	9,4 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7,2 mg KOH/g DIN ISO 3771
Sulfate ash	< 0,8 g/100g DIN 51575
Color / appearance	green, fluorescent

Areas of application

For Asian or American engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. Observe the manufacturers instructions!

Comment

⚠ WARNING: Cancer- www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions!

Available pack sizes

5 l Canister plastic	22152 USA-AND-CANADA-EN-F
205 l Black plate barrel	22154 USA-AND-CANADA-EN-F
1.000 l Container	22141 USA-AND-CANADA-EN-F

Product information

PI 39/07/04/2022



Molygen New Generation SAE 5W-20

Our information is based on thorough research and may be considered reliable, although not legally binding.