Product information

PI 40/07/22/2026

Top Tec ATF 1600



Description

Fully synthetic automatic transmission fluid, developed for exclusive use in 1st generation Mercedes-Benz 7-speed automatic transmission (up to June 2010) and also compatible with various older Mercedes-Benz 5-speed automatic transmission requirements. Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a red color.

Properties

- excellent corrosion protection
- excellent wear resistance
- excellent viscosity/temperature properties
- excellent resistance to aging
- for eliminating shifting problems
- outstanding resistance to oxidation
- outstanding friction characteristics
- very good low-temperature properties
- prevents foam formation

Specifications / Approvals

MB-Approval 236.14

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MB 236.12

Technical data

Density at 59 °F	0,85 g/cm³ DIN 51757
Viscosity at 104 °F	28,7 mm²/s ASTM D 7042-04
Viscosity at 212°F	6,45 mm²/s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	188 DIN ISO 2909
Flash point	402 °F DIN ISO 2592
Pour point	-49 °F DIN ISO 3016
Color / appearance	red

Areas of application

For Mercedes-Benz automatic transmissions where an ATF fluid meeting current product specifications is required or recommended.

Application

Observe the manufacturers instructions!Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20024 CAEN-CAFR-USEN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com