

Product information

Motorbike Speed Additive

PI 41/12/02/2021



Description

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

Properties

- higher performance gain
- improves acceleration
- cleans the fuel system
- protects fuel against oxidation and aging
- prevents corrosion in the fuel system
- prevents carburetor icing
- increases operational reliability

Technical data

Base	additive mixture in carrier fluid
Color / appearance	yellow, clear
Odor	characteristic
Form	liquid
Viscosity at 104 °F	<7 mm ² /s
Density at 68 °F	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>61 °F

Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

Comment

⚠ WARNING: Cancer- www.P65Warnings.ca.gov

Application

Contents (150 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

Available pack sizes

150 ml Can sheet metal	20108
	USA-EN
150 ml Can sheet metal	22104
	CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

