

**Special Tec V SAE 0W-30****Description**

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

**Properties**

- high shear stability
- saves fuel and reduces pollutant emissions
- ideal with turbochargers and catalytic converters
- optimum stability to aging
- outstanding engine cleanliness
- high lubrication reliability
- instant lubrication after cold start

**Specifications / Approvals**

ACEA A7/B7 • API SL • Volvo VCC 95200377

**Technical data**

SAE class (engine oils)	0W-30 SAE J300
Density at 59 °F	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	51,7 mm <sup>2</sup> /s ASTM D7042
Viscosity at 212°F	9,7 mm <sup>2</sup> /s ASTM D7042
Viscosity at -40 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at -31 °F (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	180 DIN ISO 2909
HTHS at 302 °F	2,9 - 3,5 mPas ASTM D5481
Pour point	-49 °F DIN ISO 3016
Evaporation loss (Noack)	12,0 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	12,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575

**Technical data**

Color number (ASTM)	L3,5
	DIN ISO 2049

**Areas of application**

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

**Application**

Observe the manufacturers instructions!

**Available pack sizes**

1 l Canister plastic	20202 USA-AND-CANADA-EN-F
5 l Canister plastic	20204 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**