

Motorbike 4T Synth 5W-40 Street Race

Description

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness with reduced friction and minimum wear, smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Properties

- ideal with catalytic converters
- optimum stability to aging
- high engine cleanliness
- guarantees low oil consumption
- optimum lubrication under all operating conditions
- excellent shear stability
- especially suitable for wet clutches
- excellent wear resistance

Approvals

API SN PLUS • JASO MA2

Technical data

SAE class (engine oils)	5W-40 SAE J300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	84 mm ² /s ASTM D 7042-04
Viscosity at 212°F	13,8 mm ² /s ASTM D 7042-04
Viscosity at -31 °F (MRV)	≤ 60000 mPas ASTM D4684
Viscosity at -22 °F (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 302 °F	≥ 3,5 mPas ASTM D5481
Pour point	-59 °F DIN ISO 3016
Evaporation loss (Noack)	6 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575



Technical data

Color number (ASTM)	L 2,0
	DIN ISO 2049

Areas of application

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20074 USA-AND-CANADA-EN-F
4 l Canister plastic	20076 USA-AND-CANADA-EN-F
20 l Canister plastic	20304 USA-AND-CANADA-EN-F
60 l Drum sheet metal	2593 D-GB
205 l Drum sheet metal	2594 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.