

## Motorbike 4T SAE 20W-50 Street

### Description

High quality mineral-based motor oil for ideal behavior and engine protection in all operating conditions. Provides reliable lubrication, optimum noise suppression and low wear together with perfect clutch function and smooth shifting.



### Properties

- miscible with all commercially available motor oils
- optimum stability to aging
- outstanding oil film strength
- prevents black sludge
- high wear resistance
- high shear stability
- especially suitable for wet clutches
- excellent cleaning effect
- ideal with catalytic converters
- low evaporation loss
- very good dispersion properties
- guarantees low oil consumption
- universal application

### Specifications / Approvals

API SN PLUS • JASO MA2

### Technical data

SAE class (engine oils)	20W-50 SAE J300
Density at 59 °F	0,885 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	156,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	18,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	128 DIN ISO 2909
Viscosity at 5 °F (CCS)	<= 9500 mPas ASTM D 5293
Pour point	-27 °F DIN ISO 3016
Evaporation loss (Noack)	7,9 % ASTM D 5800
Flash point	464 °F DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

### Areas of application

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

### Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

### Available pack sizes

1 l Canister plastic	20062 USA-AND-CANADA-EN-F
4 l Canister plastic	20064 USA-AND-CANADA-EN-F
20 l Canister plastic	22116 USA-AND-CANADA-EN-F
60 l Black plate barrel	22117 USA-AND-CANADA-EN-F
205 l Black plate barrel	22176 USA-AND-CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**