

Top Tec ATF 1400

Description

Fully synthetic transmission fluid with modern additive technology for use in late generation of Continuously Variable Transmissions (CVT) where torque transferring steel traction-chains or thrust link belts are used. A unique formulation offers best possible resistance to foaming, aging and oxidation.



Properties

- outstanding friction characteristics
- very good low-temperature properties
- excellent wear resistance
- prevents foam formation
- outstanding resistance to oxidation
- excellent corrosion protection
- excellent viscosity/temperature properties
- extremely stable to aging

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Dodge CVTF+4 • Dodge NS-2 • Ford CVT23 • Ford CVT30 • Ford Mercon C • GM/Saturn DEX-CVT • Honda HCF2 • Honda HMMF • Hyundai SP-CVT 1 • Jeep CVTF+4 • Jeep NS-2 • Kia SP-CVT 1 • MB 236.20 • Mini Cooper (EZL 799) • Mitsubishi CVTF-J1 • Mitsubishi CVTF-J4 • Nissan CVT NS-2 Fluid • Nissan CVT NS-3 Fluid • Subaru E-CVT • Subaru High Torque CVTF • Subaru Lineartronic CV-30 • Subaru Lineartronic CVTF • Subaru Lineartronic CVTF II • Subaru NS-2 • Suzuki CVT Green1 • Suzuki CVT Green2 • Suzuki NS-2 • Suzuki TC • Toyota CVTF FE • Toyota TC • VW G 052 180 • VW G 052 516

Technical data

Density at 59 °F	0,855 g/cm ³ DIN 51757
Viscosity at 104 °F	36,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	7,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Flash point	392 °F DIN ISO 2592
Pour point	-49 °F DIN ISO 3016
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

For Continuously Variable Transmissions (CVT) in automotive and commercial vehicles where a fluid meeting current specification is required or recommended.

Application

Observe the manufacturers instructions! Optimum efficiency and product performance are only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20036 USA-AND-CANADA-EN-F
20 l Canister plastic	20121 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.