

Central Hydraulic System Oil

Description

Fully synthetic central hydraulic system oil that meet and exceed many OE specifications. Unique formulation allows for high thermal stability and excellent resistance to aging or break down. Maximum wear protection and proper friction behavior. Has outstanding low-temperature behavior and very high corrosion-protection. The fluid is a green color.

Properties

- excellent viscosity/temperature properties
- optimum stability to aging
- highest thermal stability
- excellent low temperature behavior
- outstanding corrosion protection

Approvals

MAN M 3289

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW 81 22 9 407 758 • Fiat 9.55550-AG3 • Ford WSS-M2C 204-A • MB 345.0 • Opel 1940 766 • VW G 002 000 • VW G 004 000 • ZF TE-ML 02K

Technical data

Viscosity at 104 °F	19,6 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,4 mm ² /s ASTM D 7042-04
Viscosity index	322 DIN ISO 2909
Color / appearance	green
Density at 59 °F	0,825 g/cm ³ DIN 51757
Flash point	302 °F DIN ISO 2592
Pour point	-97 °F DIN ISO 3016
Foaming behavior at 75 °F	50/0 ml ISO 6247
Foaming behavior at 200 °F	35/0 ml ISO 6247

Areas of application

For power steering systems, hydropneumatic suspensions, shock absorbers, etc. where a hydraulic fluid meeting current product specification is required



or recommended.

Comment

⚠ WARNING: Reproductive Harm -
www.P65Warnings.ca.gov.

Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20038 USA-EN
1 l Can plastic	20326 CANADA-EN-F
20 l Canister plastic	20407 USA-AND-CANADA-EN-F
205 l Drum sheet metal	22187 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.