

Product information

Super Diesel Additive

PI 59/12/02/2021

**LIQUI
MOLY**

Description

A combination of additives to clean and maintain the diesel fuel system. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

Properties

- keeps the fuel system clean
- for low-sulfur diesel fuels
- keeps injection nozzles clean
- ideal with catalytic converters
- prevents seizing and injector gumming
- increases cetane number
- optimizes engine performance
- increases lubricating
- effective cleaning
- good corrosion protection
- guarantees low fuel consumption
- high wear resistance
- prevents the build-up of deposits

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	-32 °F
Form	liquid
Odor	characteristic

Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

Comment

⚠ WARNING: Cancer - www.P65Warnings.ca.gov.

Application

For best results and long-term effect add Super Diesel Additive every 2.000 km (1.200 miles). Contents (300 mL) is sufficient for 25–75 Liters (7 gal. to 20 gal.) fuel.

Available pack sizes

Available pack sizes

300 ml Can sheet metal	2002 USA-EN
300 ml Can sheet metal	7702 CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

