

Product information

Hydraulic Lifter Additive

PI 29/11/02/2020



Description

Prevents hydro tappet noise. Lubrication holes and ducts in the oil circuit are cleaned. Promotes the accurate function of the hydraulic lifters and reduces wear.

- damps hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil



Properties

- reduces hydraulic lifter noise
- cleans valve bores
- improves lubricating properties
- compatible for the use with turbochargers and catalytic converters

Available pack sizes

300 ml Can sheet metal	20004
	USA (-EN-)
300 ml Can sheet metal	20330
	CANADA (-EN-F-)

Technical data

Color / appearance	hellbraun / light brown
Appearance / properties	viskose Flüssigkeit / viscous liquid
Density at 68 °F	0,887 g/cm ³ DIN 51757
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 68 °F	1100 mPas

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For all gasoline and diesel engines. Can be mixed with all commercially available motor oils.

Application

One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters (1.5 gal.) motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change.

Comment

Not suitable for use on motorbikes with wet clutches.